

**First Class Millennium:
Even Future is making Progress.**



ELMECO

ADVANCED SOLUTIONS FOR COLD BEVERAGE
SINCE 1961



First Class Millennium: First Class Evolution

First Class Millennium is the slush machine that goes beyond the future. The already advanced functions of First Class were further implemented with the new electronics that makes it easier for the user to approach the new machine functions.



First Class Millennium: The Implemented Features

- density control
- more "easy to read" alarms
- emergency and backup procedures
- date & time
- part number memorization
- first 24 hours operation date memorization
- operation hours counting
- "low level" control
- "defrost" function
- max time between two subsequent cleaning procedures control
- "automatic block" period setting
- "critical temperature" control



First Class Millennium: A Reprogrammable Core.

Thanks to the "Programming Module" (optional) First Class Millennium, can be reprogrammed with the functions set up in our factory according to the needs of the user or of a machine cluster manager; for example: defrost time, date and time (for different time zones), automatic block times...

First Class Millennium: An Investment for the Future.

Thanks to the new "Machine module" electronic interface, the machine control software can be subsequently upgraded by simply connecting it to a computer through a dedicated software. This operation grants that today's investment will be safeguarded for long, thanks to the possibility to have a machine that is always behind the times.

Modello/Model	FC3 Millennium	FC3 Millennium US	FC2 Millennium	FC2 Millennium US
Altezza/Height	780 mm	30,7 in	780 mm	30,7 in
Larghezza/Width	620 mm	24,4 in	430 mm	16,9 in
Profondità/Depth	560 mm	22,0 in	560 mm	22,0 in
Peso/Weight	64 Kg	141,1 lb	52 Kg	114,6 lb
Capacità/Capacity	12 l x 3 (36 l)	3,17 gal x 3 (9,51 gal)	12 lt x 2 (24 l)	3,17 gal x 2 (6,34 gal)
Potenza/Power	1200 W	1,63 hp	900 W	1,22 hp
Voltaggio/Hz-Voltage/Hz	230V/50 220V/60 115V/60	230V/50 220V/60 115V/60	230V/50 220V/60 115V/60	230V/50 220V/60 115V/60

Our company reserve the right to make changes without any notice.